



All-In-One Power Bank 600 Watt Hours

TAA COMPLIANT



ITEM	SPECIFICATION
P/N	AIO48A
Battery Nominal voltage	12.8 Vdc
Capacity	48Ah (614Wh)
Battery Type	Lithium Iron Phosphate (LiFePO4)
Input	DC 12V~15V
Vehicle Charging Max voltage/current	14.6V / 24A (optional cable required)
12V Receptacle (Cigarette) In/out	DC 11V~15V (Max.10A)
Solar MPPT input, Maximum V/W	50Vdc / 200W
AC Inverter, Pure Sine Wave	600 Watts (1,000 W surge) 110V / 60Hz 2 AC outlets
USB Outputs	Qty 1: Type-C, Qty 1: Type-A
DC Output	DC 10 – 14.6V (Max 200A)
	Qty 1: 12V power sockets
	DC Jack 5.50mm & 2.1mm
Cycle Life	3,000 + cycles >80% DOD (Depth of Discharge)
Charging Temperature Range	0C to 45C (0F to 113F)
Discharge Temperature Range	-20C to 60C (-4F to 140F)
Dimensions	18.25"L X 4.5"W X 8.75"H
Weight	21 lbs

CIGAR Charger DC 11V~15V



LFP Charger 14.6V 10A

